

WHAT IS CLAIMED IS:

1. A method for streaming scalable video including base layer data and enhancement layer data, comprising the steps of:  
transmitting the base layer data for a given interval;  
determining if a loss of bandwidth has occurred in the given

5 interval;

selecting a predetermined number of frames to distribute the loss of bandwidth over;

calculating a reduced amount of enhancement layer data to transmit in the predetermined number of frames; and

10 transmitting the reduced amount of enhancement layer data in the given interval.

Sub A1  
2. The method according to claim 1, further comprising transmitting non-enhancement layer data during the given interval.

3. The method according to claim 1, wherein the calculating step is performed so that the loss of bandwidth is distributed evenly over the predetermined number of frames.

4. The method according to claim 1, further comprising the steps of:

determining if there is still space in the given interval; and  
transmitting at least a portion of the reduced amount of

5 enhancement layer data from a second given interval in the given interval.

5. The method according to claim 1, further comprising the steps of:

determining if the predetermined number of frames has expired;  
determining if any left-over enhancement layer data exists;

5 selecting a second predetermined number of frames to distribute the left-over enhancement layer data over;

calculating a second reduced amount of enhancement layer data

to transmit in the second predetermined number of frames; and  
transmitting the second reduced amount of enhancement layer  
10 data in a second given interval.

6. The method according to claim 1, wherein the enhancement  
layer data has a fine grain scalability structure.

31  
7. A method for streaming scalable video including base layer  
data and enhancement layer data, comprising the steps of:  
transmitting the base layer data for a given interval;  
selecting a predetermined number of frames if a loss of  
5 bandwidth has occurred in the given interval;  
distributing the loss of bandwidth over the predetermined  
number of frames to produce a reduced amount of enhancement layer  
data; and  
transmitting the reduced amount of enhancement layer data in  
10 the given interval.

8. The method according to claim 7, wherein the distributing  
step is performed so that the loss of bandwidth is distributed  
evenly over the predetermined number of frames.

9. A memory medium including code for streaming scalable video  
including base layer data and enhancement layer data, the code  
comprising:

a first transmitting code to transmit the base layer data for a  
5 given interval;

a determining code to determine if a loss of bandwidth has  
occurred in the given interval;

a selecting code to select a predetermined number of frames to  
distribute the loss of bandwidth over;

10 a calculating code to calculate a reduced amount of enhancement  
layer data to transmit in the predetermined number of frames; and

a second transmitting code to transmit the reduced amount of  
enhancement layer data in the given interval.

Sub A2

10. An apparatus for streaming scalable video including a base layer and an enhancement layer, comprising:

a memory which stores executable code; and

a processor which executes the code stored in the memory so as

- 5 to (i) transmit the base layer data for a given interval, (ii) determine if a loss of bandwidth has occurred in the given interval, iii) select a predetermined number of frames to distribute the loss of bandwidth over, iv) calculate a reduced amount of enhancement layer data to transmit in the predetermined number of frames, and v)
- 10 transmit the reduced amount of enhancement layer data in the given interval.

11. An apparatus for streaming scalable video including a base layer and an enhancement layer, comprising:

means for transmitting the base layer data for a given interval;

- 5 means for determining if a loss of bandwidth has occurred in the given interval;

means for selecting a predetermined number of frames to distribute the loss of bandwidth over;

- 10 means for calculating a reduced amount of enhancement layer data to transmit in the predetermined number of frames; and

means for transmitting the reduced amount of enhancement layer data in the given interval.

ADD A3